



ADURA LMP

PRODUCT DESCRIPTION:

ADURA LMP is a versatile, general-purpose lubricating grease formulated with a lithium hydroxystearate soap thickener and premium mineral base oil. It is enhanced with antioxidants, rust and corrosion inhibitors, and anti-wear additives. This grease is recommended for lubricating rolling element bearings, electric motor bearings, water pumps, and sealed-for-life bearings. Available in NLGI 1 and NLGI 2 grades, it is designed for general industrial applications and is compatible with centralized lubrication systems operating at normal temperatures.

APPLICATION

ADURA LMP is recommended for the lubrication of rolling-element bearings, electric motor bearings water pumps, and sealed-for-life bearings. These greases are designed for general industrial lubrication which can be used through centralized lubrication systems operating at normal temperatures.

PRODUCT ADVANTAGES

- The operating temperature range is -20°C to 130°C
- Good oxidation and mechanical stability
- Reliable high-temperature performance
- Long storage life
- Good rust and corrosion protection

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE					
NLGI Grade	-	000	00	0	1	2	3
Thickener Type	-	Lithium 12-Hydroxystearate					
Appearance	Visual	Smooth & Homogenous					
Color	Visual	Yellow to Brown					
Work Penetration @25°C	ASTM D217	445-475	400-430	355-385	310-340	265-295	220-250
Copper Strip Corrosion For 24hrs @100°C	ASTM D4048	1b max.	1b max.	1b max.	1b max.	1b max.	1b max.
Dropping Point °C, Min	ASTM D2265	N/A	N/A	N/A	180	180	180
Water Washout Resistance %Wt @79°C	ASTM D1264	N/A	N/A	N/A	Max 10		
Emcor Rust Preventive Test	ASTM D6138	Pass					
Operating Temperature Range, °C	INTERNAL	-20 to 130					
Base Oil Viscosity @40°C (Cst)	ASTM D445	90-110					

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.