



ALTUS 2T

2 STROKE ENGINE OIL

PRODUCT DESCRIPTION:

ALTUS 2T is a high-performance lubricant designed for two-stroke engines in motorcycles, scooters, and mopeds. Its formulation is fully compatible with lead-free fuels. This advanced product combines a precise balance of highly refined base oils and cutting-edge additives. It is specially designed for use in both oil-injected and pre-mixed gasoline/oil lubricated engines. With enhanced performance, ALTUS 2T provides excellent protection against exhaust emissions and reduces engine carbon deposits.

APPLICATION:

ALTUS 2T oil is designed for use in two-stroke air-cooled engines. It is also suitable for motorcycles, scooters, mopeds, snowmobiles, lawnmowers, golf carts, chainsaws, and other two-stroke powered equipment where API TC lubricants are recommended. This product should be used according to the OEM-recommended fuel/oil mix ratio. If no specific ratio is provided, the general recommendation is a 50:1 fuel/oil mix.

FEATURES & BENEFITS:

- Provides piston scuffing protection and reduces smoke
- Thermal and oxidation stability
- Specially formulated to avoid spark plug fouling
- Perfectly adapted to unleaded fuel
- Protection against pre-ignition problems

PERFORMANCE LEVEL: Meets or Exceeds:

- API TC
- JASO FD
- ISO EGD

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	ALTUS 2T
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	9
Viscosity Index	ASTM D2270	-	120
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR
Flash Point (min)	ASTM D92	°C	220
Pour Point (max)	ASTM D97	°C	-24
Color	Visual	-	Blue

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.