



## ALTUS 4T ULTRA

SYNTHETIC / SEMI SYNTHETIC / MINERAL

### PRODUCT DESCRIPTION:

ALTUS 4T ULTRA is a multi-grade oil formulated for four-stroke engines in motorcycles, scooters, and mopeds. Blended with high-quality base oils and a well-balanced additive system from leading manufacturers, it offers enhanced detergency, anti-wear protection, and anti-foam properties. Additionally, ALTUS 4T ULTRA provides superior resistance to oxidation and corrosion, ensuring long-lasting engine performance and protection.

### APPLICATION:

ALTUS 4T ULTRA is designed for use in four-stroke engines of scooters, mopeds, motorcycles, and ATVs that require an API SG performance level. It is also suitable for lubricating the transmissions and clutches of motorcycles that depend on motor oil for proper lubrication.

### FEATURES & BENEFITS:

- Maximum engine power.
- Unsuper passed gear protection.
- Outstanding wear protection
- Excellent shear and oxidation resistance
- Better clutch "feeling"
- Excellent low temperature fluidity

### PERFORMANCE LEVELS: Meets or Exceeds:

- API SG
- JASO MA

### TYPICAL PROPERTIES:

| PARAMETERS                          | TEST METHOD | UNIT  | ALTUS 4T ULTRA |        |        |        |        |        |        |        |
|-------------------------------------|-------------|-------|----------------|--------|--------|--------|--------|--------|--------|--------|
|                                     |             |       | 5W-30          | 10W-30 | 10W-40 | 10W-50 | 15W-40 | 15W-50 | 20W-40 | 20W-50 |
| Grade                               |             |       |                |        |        |        |        |        |        |        |
| Kinematic Viscosity @ 104°F / 40°C  | D7042       | cSt   | TBR            | TBR    | TBR    | TBR    | TBR    | TBR    | TBR    | TBR    |
| Kinematic Viscosity @ 212°F / 100°C | D7042       | cSt   | 11.7           | 11.7   | 15.1   | 19.5   | 15     | 19.5   | 15     | 20     |
| Viscosity Index (min)               | D2270       | -     | 160            | 145    | 145    | 145    | 135    | 135    | 120    | 120    |
| Density@15°C/ 60°F                  | D4052       | g/cm3 | TBR            | TBR    | TBR    | TBR    | TBR    | TBR    | TBR    | TBR    |
| Flash Point (min)                   | D92         | °C    | 220            | 220    | 220    | 220    | 220    | 220    | 220    | 220    |
| Pour Point (max)                    | D97         | °C    | -39            | -36    | -36    | -36    | -33    | -33    | -24    | -24    |

**DISCLAIMER:** The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: [www.alphaoil.ae](http://www.alphaoil.ae)

### HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. [www.alphaoil.ae](http://www.alphaoil.ae)

### PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

### STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.