



ALTUS 4T

SYNTHETIC / SEMI SYNTHETIC / MINERAL

PRODUCT DESCRIPTION:

ALTUS 4T is highly recommended for high-performance 4-stroke motorcycles, delivering exceptional power efficiency and acceleration. It surpasses fuel economy and engine cleanliness standards while providing outstanding engine protection and superior clutch performance in all riding conditions. Additionally, ALTUS 4T helps maintain peak engine power and supports extended drain intervals for enhanced durability and convenience.

APPLICATION:

Recommended for all motorcycles with 4T engines. Suitable for Honda, Yamaha, Suzuki, Kawasaki, Korean and Chinese motorcycles.

FEATURES & BENEFITS:

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

PERFORMANCE LEVELS: Meets or Exceeds:

- API SJ
- JASO MA

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	ALTUS 4T						
			5W-40	10W-30	10W-40	10W-60	20W-40	20W-50	20W-60
Grade									
Kinematic Viscosity @ 104°F / 40°C	ASTM D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F / 100°C	ASTM D7042	cSt	14.8	11.9	14.7	24.9	14.9	19.8	23.5
Viscosity Index (min)	ASTM D2270	-	160	145	145	145	120	120	120
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	ASTM D92	°C	220	220	220	220	220	220	220
Pour Point (max)	ASTM D97	°C	-39	-36	-36	-36	-24	-24	-24

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.