



ALTUS SHOCK ABSORBER OIL

PRODUCT DESCRIPTION:

ALTUS SHOCK ABSORBER OIL is formulated with high-performance synthetic base oils and a blend of additives to deliver exceptional damping performance for shock absorbers in motorcycles. This oil offers excellent viscosity temperature stability, oxidation resistance, and anti-foam properties. Additionally, it provides excellent compatibility with seals, ensuring reliable performance and protection in all conditions.

APPLICATION:

Recommended as hydraulic fluid for front fork motorcycles & other shock absorbers mechanism.

FEATURES & BENEFITS:

- Increase the life of shock absorber
- Excellent seal compatibility
- Longer oil life
- Excellent damping effect
- Excellent low temperature properties

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	ALTUS SHOCK ABSORBER OIL
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	32
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	5.9
Viscosity Index	ASTM D2270		130
Flash Point (min)	ASTM D92	°C	210
Pour Point	ASTM D97	°C	-24

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.