



AQUENT G13 PRO PSI-OAT COOLANT

PRODUCT DESCRIPTION:

AQUENT G13 PRO is a high-quality, premixed ready-to-use coolant that protects the cooling system by utilizing organic acid technology combined with silicate and phosphate. Designed to meet the specific needs of modern Volkswagen Group engines, it offers exceptional corrosion protection and long-lasting performance, even under extreme thermal conditions. This updated version of the G13 coolant is backward compatible, replacing G13 and G12 coolants, and can be safely mixed with all other VW coolants (G11, G12, G12+, G13).

APPLICATION:

AQUENT G13 PRO meets the special requirements of modern engines of the Volkswagen Group.

FEATURES & BENEFITS:

- Outstanding corrosion protection.
- Contains no amines, nitrites or phosphates.
- Universal application at passenger cars and commercial vehicles.
- Anti-cavitation, preventing foam and the retention of air, ensuring the good performance of the pump.
- Prevents the build-up of deposits, keeping the cooling system clean.
- Long life service product

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- Bentley (TL 774-L)
- Audi (TL 774-L)
- Bugatti (TL 774-L)
- Deutz (DQC CC-14)
- Lamborghini (TL 774-L)
- Porsche (TL 774-L)
- Seat (TL 774-L)
- Skoda (TL 774-L)
- Volkswagen (VW) (TL774-L)
- AS 2108-2004
- ASTM D 3306
- ASTM D 4985
- BS6580:2010
- CUNA NC 956-16
- PN-C40007:2000
- SAE J1034
- ÖNORM V5123
- SANS 1251:2005
- China GB 29743-2013

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	AQUENT G13 PRO
pH	D1278	cSt	8
Freezing Point	D1177	°C	-37
Boiling Point	D1120	cSt	110
Density at 15.5C	D4052	g/cm3	TBR

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.