



AQUENT HOAT

PREDILUTED COOLANT/ANTIFREEZE

PRODUCT DESCRIPTION:

AQUENT HOAT is a premixed antifreeze formulated with Hybrid Organic Acid Technology (HOAT) to offer protection against rust and corrosion in the cooling systems of automobiles and trucks, including American, Asian, and European vehicles. This product is designed to be phosphate-free and does not contain 2-Ethylhexanoic acid (2EH).

APPLICATION:

AQUENT HOAT is recommended for applications where equipment's manufacturers recommend HOAT type coolant/antifreeze.

FEATURES & BENEFITS:

- Designed for use in engines running EGR and SCR technologies that can increase cooling system temperatures
- Eliminates the cost of SCAs
- Fully compatible with other quality Organic Acid (OAT) and Nitrite Organic Acid (NOAT) heavy-duty extended life coolants
- Non-abrasive formula can improve water pump seal life
- Optimal hard water compatibility and reduced hard water scale
- Provides outstanding long-term elastomer compatibility

PERFORMANCE LEVELS: Meets or Exceeds:

- ASTM D3306, D4985, D6210
- BS 6580
- SAE J1034, J1941
- FORD WSS-M97B51-A1
- ANFOR NF R 15-601
- CATERPILLAR (DEAC)
- CHRYSLER MS 7170
- CUMMINS
- DETROIT DIESEL
- JIS K 2234
- JOHN DEERE H-5, H24B1, H24C1
- TMC RP329, RP330

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	AVALANCHE HOAT
Freezing Point	ASTM D1177	°C	-37
pH	ASTM D1287	-	8 - 10
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.