



ARVO CLASSIC SEMI SYNTHETIC

PRODUCT DESCRIPTION:

ARVO CLASSIC Semi Synthetic is a heavy-duty engine oil designed to deliver excellent lubrication for both diesel and gasoline engines operating in severe conditions. Formulated with high-performance base oils, it offers exceptional low-temperature fluidity, high-temperature viscosity retention, and volatility control. ARVO CLASSIC is engineered to provide strong oxidation resistance, effective soot handling, and wear protection. It also offers excellent piston deposit protection and reduces sludge formation, contributing to extended engine life.

APPLICATION:

ARVO CLASSIC Semi Synthetic delivers proven protection and performance in the latest high-power heavy-duty diesel engines from European, U.S., and Japanese manufacturers, across both on-highway and off-highway applications. It is suitable for modern low-emission engines that meet Euro 2, Euro 3, and U.S. 2002 emission standards.

FEATURES & BENEFITS:

- Increased thermal and oxidation stability
- Reduced sludge build-up, deposits and extended engine life
- Improved corrosion protection and advanced piston deposit control
- Advanced soot handling to control viscosity increase and sludge build up
- Enhanced low temperature pumpability

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API CI-4/SL
- ACEA E7, A3/B3/B4
- DTRF 15B110 / 229.1
- MAN M3275-1
- Volvo VDS-3
- Deutz DQC III-10
- JASO DH1
- MACK EO-N
- Cummins CES 20076/20077/78
- Global DHD1
- Renault RLD2
- MTU Type 2
- Allison C4
- Caterpillar ECF 1a, ECF 2
- DDC 93K215

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	ARVO CLASSIC	
			10W-30	10W-40
Grade				
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.7	15.1
Viscosity Index (min)	D2270	-	145	145
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-36	-36

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.