



ASTRA G9000 MINERAL

PRODUCT DESCRIPTION:

ASTRA G9000 is a premium-quality mineral oil for gasoline and diesel engines, suitable for all driving conditions, including city traffic, highways, and motorways. It is especially recommended for turbocharged engines and is fully compatible with vehicles equipped with catalytic converters and running on unleaded fuel.

APPLICATION:

Recommended for naturally aspirated and turbocharged gasoline engines in passenger cars, light commercial vehicles, four-stroke gasoline engines, and portable power equipment.

FEATURES & BENEFITS:

- High viscosity index
- Excellent viscosity stability
- Excellent detergency and dispersancy
- Very high antiwear and anticorrosion properties
- Very good antioxidant, antirust, antifoaming properties

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	15W-40	20W-50	20W-60	25W-60
API	SL/CF	SL/CF	SL/CF	SL/CF
ACEA-23	A3/B3	A3/B3	A3/B3	A3/B3
RENAULT	RN0700/ RN0710	RN 0700/0710	-	-
VW	501.01 / 505	501.01 / 505	501.01 / 505	-

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	ASTRA G9000			
			15W-40	20W-50	20W-60	25W-60
SAE Grades						
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D445	cSt	15	20.2	24.2	24.0
Viscosity Index (min)	D2270	-	142	131	145	124
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220
Pour Point (max)	D97	°C	-33	-24	-24	-21

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.