



ASTRA G9000 SEMI SYNTHETIC

PRODUCT DESCRIPTION:

ASTRA G9000 semi-synthetic motor oil is formulated with advanced additive technology to deliver superior cleaning and protection. This multigrade lubricant is designed to perform reliably under demanding conditions, including highway driving and heavy urban traffic, in all seasons.

APPLICATION:

ASTRA G9000 is designed for modern, high-performance gasoline and diesel engines in passenger cars, minibuses, and light trucks, meeting the API SL/CF performance standards.

FEATURES & BENEFITS:

- Superior wear and corrosion protection
- Protects against start-up wear in cold conditions through excellent low-temperature fluidity
- Maintains power and economy by minimizing wear
- Superior viscosity retention
- Oxidation resistant
- Engine Cleanliness and low combustion residue

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	10W-30	10W-40	10W-60
API	SL/CF	SL/CF	SL/CF
ACEA-23	A3/B3	A3/B3	A3/B3
MB	-	229.3	-
RENAULT	RN0700/ RN0710	RN 0700/0710	-
VW	501.01 / 505	501.01 / 505	501.01 / 505

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	ASTRA G9000		
SAE Grades			10W-30	10W-40	10W-60
Kinematic Viscosity @ 104°F / 40°C	D445	cSt	TBR	TBR	TBR
Kinematic Viscosity @ 212°F / 100°C	D445	cSt	11.8	15	24
Viscosity Index (min)	D2270	-	145	145	145
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220
Pour Point (max)	D97	°C	-36	-36	-36

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.