



ASTRA GTX FULLY SYNTHETIC

PRODUCT DESCRIPTION:

ASTRA GTX is a high-performance fully synthetic engine oil designed for superior performance in high-powered engines. It offers exceptional oil film strength, outstanding engine cleanliness, excellent wear protection, and long-lasting durability. Specially formulated for the latest-generation gasoline and diesel engines—whether naturally aspirated or turbocharged, with direct or indirect injection—it meets ACEA C3 specifications. ASTRA GTX is also compliant with EURO VI emission standards.

APPLICATION:

It is recommended for high-performance engines fitted with GPF (gasoline particulate filter) and SCR (Selective Catalyst Reduction), requiring an ACEA C3 engine oil. It is not backward compatible with vehicle engines requiring an A40, C30 or C20 specifications lubricant.

FEATURES & BENEFITS:

- Active detergent system helps to prevent build-up of deposits and sludge.
- Excellent thermal oxidation stability helps to reduce oil aging.
- Provides outstanding wear protection.
- Excellent cold flow properties helps to provide protection at start up..
- Enhanced frictional properties provide fuel economy improvement.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-40	5W-40
API	SN	SN
ACEA-23	C3	C3
MB	229.31, 229.52, 226.5	229.31, 229.52, 226.5
BMW	LL-04	LL-04
RENAULT	RN 0700/0710	RN 0700/0710
GM	DEXOS 2	DEXOS 2
PORSCHE	C40	C40
VW	511 00	511 00
FIAT	9.55535-S2/9.55535-T2	9.55535-S2/9.55535-T2

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	ASTRA GTX	
SAE Grades			0W-40	5W-40
Kinematic Viscosity @ 104°F / 40°C	D445	cSt	TBR	TBR
Kinematic Viscosity @ 212°F / 100°C	D445	cSt	14.1	13.9
Viscosity Index (min)	D2270	-	170	160
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-39	-39

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.