



ASTRA GX PLUS SYNTHETIC

PRODUCT DESCRIPTION:

ASTRA GX PLUS is a high-performance fully synthetic engine oil engineered to provide exceptional protection for modern gasoline and diesel engines, whether naturally aspirated or turbocharged, with indirect or direct injection. It meets the latest industry standards for "Full SAPS" passenger car lubricants and surpasses conventional oils in performance. Designed for enhanced oxidation resistance, superior deposit and wear protection, and excellent low-temperature performance throughout its lifespan.

APPLICATION:

Suitable for all type of fuels: leaded or unleaded Gasoline, Ethanol, LPG, Diesel and biofuels. Compatible for catalytic converters.

FEATURES & BENEFITS:

- Quick cold weather starting and fast protection helps extend engine life
- Outstanding thermal and oxidation stability
- Used for all high-performance gasoline engine cars equipped with direct-injection, multi-valve, and turbo-charged technologies.
- Formulated for optimum viscosity control

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-20	0W-30	0W-40	5W-20	5W-30	5W-40
API	SN	SL/CF	SN/CF	SN	SN/SL/CF	SN/CF
ACEA-23	A5/B5	A3/B4	A3/B4	A5/B5	A3/B4	A3/B4
VOLVO	-	95200356	-	-	-	-
Porsche	-	-	A40	-	-	A40
MB	-	226.5 229.3 229.5	226.5 229.3 229.5	-	226.5 229.3 229.5	226.5 229.3 229.5
RENAULT	-	RN0700 RN0710	RN0700 RN0710	-	RN0700 RN0710	RN0700 RN0710
VW	-	502 00 505 00	502 00 505 00	-	502 00 505 00	502 00 505 00
BMW	-	LL-01	LL-01		LL-01	LL-01
PSA	-	-	-	-	-	B71 2296
Ford	-	-	WSS-M2C-937-A	WSS-M2C-925-B	-	-
LANDROVER	-	-		STJLR.03.5004	-	-



TYPICAL SPECIFICATION:

PARAMETERS	ASTM	UNIT	ASTRA GX PLUS					
Grade			0W-20	0W-30	0W-40	5W-20	5W-30	5W-40
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	8.9	11.8	14.9	8.8	11.6	15
Viscosity Index (min)	D2270	-	150	160	170	150	160	160
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220	220	220
Pour Point (max)	D97	°C	-39	-39	-39	-39	-39	-39

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.