



ASTRA GX PRO

FULLY SYNTHETIC / SEMI SYNTHETIC / MINERAL

PRODUCT DESCRIPTION:

ASTRA GX PRO is a high-performance lubricant enhanced with a proven metallo-organic anti-wear additive system, providing exceptional protection under all operating conditions. It offers excellent wear control, even in the most advanced valve train systems, including those with variable valve timing. Expertly engineered to deliver superior cleaning power, wear protection, and outstanding performance, ASTRA GX PRO helps resist oil degradation between oil changes, extending the time and mileage interval between services.

APPLICATION:

Recommended for gasoline fueled automobiles and light duty trucks requiring an oil meeting API SN/CF specification.

FEATURES & BENEFITS:

- Outstanding wear protection under a wide variety of operating conditions.
- Special cleaning additive to help prevent the formation of sludge and harmful deposits.
- Optimal engine operating temperature, owing to thermal control formula.
- Limits formation of deposits on the most loaded engine parts.
- Provides safe operation of catalytic exhaust converters.
- Resistant to extreme thermal load, due to high quality of base oil.
- Enables fast and easy start in extreme temperature conditions.
- High performance extended drain formulation helps offer optimum engine uptime.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-20	5W-20	5W-30	5W-40	10W-30	10W-40	15W-40	20W-50
API	SN/CF	SN/CF	SN/CF	SN/CF	SN/CF	SN/CF	SN/CF	SN/CF
ILSAC	GF-5	GF-5	-	-	-	-	-	-
ACEA-23	-	-	A3/B4-12	A3/B4-12	A3/B4-12	A3/B4-12	A3/B4-12	A3/B4-12
MB	-	-	229.3	229.3	229.3	229.3	229.3	229.3
VW			502 00/ 505 00	502 00/ 505 00				
RENAULT			700/710	700/710	700/710	700/710	700/710	700/710

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	ASTRA GX PRO							
			0W-20	5W-20	5W-30	5W-40	10W-30	10W-40	15W-40	20W-50
Grade										
Kinematic Viscosity @ 104°F / 40°C	ASTM D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F / 100°C	ASTM D7042	cSt	8.4	8.5	11.8	15	11.8	15.1	15.4	20.1
Viscosity Index (min)	ASTM D2270	-	150	150	160	160	145	145	135	120
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	ASTM D92	°C	220	220	220	220	220	220	220	220
Pour Point (max)	ASTM D97	°C	-39	-39	-39	-39	-36	-36	-33	-24

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.