



ASTRA XTL FULLY SYNTHETIC

PRODUCT DESCRIPTION:

ASTRA XTL is a high-performance, fully synthetic MID SAPS lubricant designed for both gasoline and diesel engines, including those meeting the ACEA C2/C3 standard. It is formulated to reduce pollutant emissions such as HC, NOx, CO, and particles, while also protecting and enhancing the longevity of after-treatment anti-pollution systems like Gasoline Particulate Filters (GPF), Diesel Particulate Filters (DPF), and Three-Way Catalysts. With synthetic base oils and the latest additive technology, ASTRA XTL provides exceptional wear protection and helps reduce both oil and fuel consumption.

APPLICATION:

This product meets or exceeds the requirements of the latest API and ACEA industry specifications for petrol engine oils, as well as the requirements of many major American and European engine manufacturers. Suitable for use in both gasoline and diesel passenger cars and light commercial vehicles.

FEATURES & BENEFITS:

- Excellent engine cleanliness
- Excellent cold flow properties
- Engine protection under a wide variety of operating conditions
- Optimum power & performance under most severe driving conditions
- Fully compatible with all emission control devices.
- Helps protect engine against wear and corrosion
- Allows fuel consumption reduction and therefore minimizes green house gases emissions.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

	SAE GRADES	5W-40	5W-30
API		SN PLUS/ SP	SN PLUS/ SP
ACEA-23		C3	C3/C2
BMW		LL-04	LL-04
MB		229.51 / 229.52	229.51 / 229.52
OPEL		OV 040 1547	OV 040 1547
RENAULT		RN0700/RN0710	RN0700/RN0710

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	ASTRA XTL	
Grade			5W-40	5W-30
Kinematic Viscosity @ 104°F / 40°C	D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F / 100°C	D7042	cSt	13.5	11.8
Viscosity Index (min)	D2270	-	160	160
Density@15°C/ 60°F	D4052	g/cm³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-39	-39

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.