



ATRIX LCEP 220

PRODUCT DESCRIPTION:

ATRIX LCEP 220 is an extreme-pressure grease fortified with a solid lubricant, offering exceptional resistance to water washout and providing excellent protection against wear and corrosion. It is ideal for lubricating shock-loaded, heavy-duty bearings operating in wet conditions. This grease is also suitable for off-road applications and fifth-wheel lubrication, ensuring reliable performance in challenging environments.

APPLICATIONS

ATRIX LCEP 220 is recommended for the lubrication of shock-loaded, heavy duty bearings working in wet conditions. It is also suitable for off-road applications and fifth-wheel lubrication.

PRODUCT ADVANTAGES

- The operating temperature range is from -25°C to 130°C
- Effective extreme pressure properties
- Enhanced load-carrying and wear protection properties
- Good pumpability
- Good water washout properties

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE
NLGI Grade	-	2
Thickener Type	-	Lithium - Calcium
Base Oil Type	-	Mineral
Appearance	Visual	Smooth & Homogenous
Color	Visual	black
Work Penetration @25°C	ASTM D217	265-295
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b
Dropping Point, °C, Min	ASTM D2265	180
Four Ball Weld Load, Kgf, Min	IP 239	315
Operating Temperature Range °C	INTERNAL	-25 to 130
Base Oil Viscosity @40°C (Cst)	ASTM D-445	220

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.