



ATRIX LXEP 460

PRODUCT DESCRIPTION:

ATRIX LXEP 460 is a mineral oil-based grease with excellent extreme pressure performance. It is recommended for general industrial and automotive applications where loads or temperatures exceed the capabilities of standard greases. This grease is particularly suitable for lubricating heavy-duty, slow-moving bearings in industries such as steel, cement, paper, chemicals, and mining, offering reliable performance under demanding conditions.

APPLICATIONS

ATRIX LXEP 460 is particularly recommended for grease lubrication of heavy duty, slow moving bearings used in heavy industries e.g. steel, cement, paper, chemical industry and mining.

PRODUCT ADVANTAGES

- The operating temperature range is -20°C to 150°C
- High base oil viscosity for slow moving large bearings
- Excellent mechanical stability
- Excellent extreme pressure properties
- Excellent water resistance and effective corrosion properties
- High dropping point

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE
NLGI Grade	-	2
Thickener Type	-	Lithium Complex
Base Oil Type	-	Mineral
Appearance	Visual	Smooth & Homogenous
Color	Visual	Light brown
Work Penetration @25°C	ASTM D217	265-295
Copper Strip Corrosion For 24hrs @100°C	ASTM D4048	1b
Dropping Point °C, Min	ASTM D2265	250
Four Ball Weld Load Kgf, Min, Min	ASTM D2596	250
Four Ball, Wear Scar Dia, mm, Max	ASTM D2266	0.6
Operating Temperature Range °C	INTERNAL	-20 to 150
Base Oil Viscosity @40°C (Cst)	ASTM D445	460

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.