



ATRIX PU 100

PRODUCT DESCRIPTION:

ATRIX PU 100 is a multipurpose, high-temperature, extreme pressure grease specifically formulated to provide reliable lubrication for highly loaded ball, roller, and plain bearings at elevated temperatures, ensuring extended service life. It is highly recommended for use in industries such as paper, steel, aluminum, chemicals, and other demanding applications, offering exceptional performance under extreme conditions.

APPLICATIONS

ATRIX PU 100 grease NLGI-2 is also recommended for paper, steel, aluminum, chemical and other industries.

PRODUCT ADVANTAGES

- The operating temperature range is -10°C to 150°C
- Outstanding high-temperature oxidation stability
- Reduced grease consumption at high temperatures
- Protects bearings against wear under conditions of shock loading
- Resists water washing and rusting
- Long operational life

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE
NLGI Grade	ASTM D217	2
Thickener Type	-	Di- Urea
Base Oil Type	-	Mineral
Appearance	Visual	Smooth & Homogenous
Color	Visual	Light Brown
Work Penetration, 0.1 mm	ASTM D217	265-295
Dropping Point, °C, Min	ASTM D2265	>250
Cu Corrosion	ASTM D4048	1b
Oxidation Stability, Drop In Pressure, Psi	ASTM D942	max 5
Heat Stability, % Wt.	ASTM D6184	3 max
Operating Temperature Range °C	INTERNAL	-10 to 150
Base Oil Viscosity @40°C (Cst)	ASTM D445	100

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.