



ATRIX PU 460

PRODUCT DESCRIPTION:

ATRIX PU 460 is an extreme-pressure grease engineered to provide superior lubrication in heavily loaded, low to medium-speed industrial bearings, particularly in continuous steel casting lines. It is also ideal for lubricating high-temperature, slow-moving concast bearings in the steel industry, as well as other high-temperature, slow-moving bearing applications, offering excellent performance and protection under demanding conditions.

APPLICATIONS

ATRIX PU 460 grease NLGI 1.5 is designed to give enhanced lubrication in loaded low to medium-speed industrial bearings, especially in continuous steel casting lines. It is also recommended for the lubrication of high-temperature, slow-moving concast bearings in steel industry.

PRODUCT ADVANTAGES

- The operating temperature range is -10°C to +150°C
- Outstanding high-temperature oxidation stability
- Good anti-corrosion properties
- Excellent resistance against water washout
- Long operational life

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE
NLGI Grade	ASTM D217	1.5
Thickener Type	-	Di- Urea
Base Oil Type	-	Mineral
Appearance	Visual	Smooth & Homogenous
Color	Visual	Light Brown
Work Penetration, 0.1mm	ASTM D217	305
Dropping Point, °C, Min	ASTM D2265	250
Cu Corrosion	ASTM D4048	1b
Four Ball Weld Load, Kgf, Min	ASTM D2596	250
Emcor Rust Test, Rating	IP 220	0-0
Heat Stability, %Wt.	ASTM D6184	3 max
Operating Temperature Range °C	INTERNAL	-10 to 150
Base Oil Viscosity @40°C (Cst)	ASTM D445	460

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.