



ATRIX SYN LCEP 150

PRODUCT DESCRIPTION:

ATRIX SYN LCEP 150 is a synthetic grease containing 5% MoS₂, designed for extreme pressure and multi-purpose use in mining and construction equipment. This grease provides robust protection for sustained heavy-duty operations. Its advanced formulation ensures excellent mobility, even in Arctic winter conditions. ATRIX SYN LCEP 150 is engineered for outstanding all-around performance, offering a balanced combination of mobility, load-carrying capacity, and long service life.

APPLICATIONS

ATRIX SYN LCEP 150 is an extreme pressure, multi-purpose, mining, and construction equipment grease, which offers protection from sustained heavy-duty operations.

PRODUCT ADVANTAGES

- The operating temperature range is from -40 to 130
- Outstanding high-temperature oxidation stability
- Excellent extreme pressure properties
- High dropping point
- Effective corrosion protection
- Long operational life

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE	
		0/00	1
NLGI Grade	-		
Thickener Type	-	Lithium-calcium	Lithium-calcium
Base Oil Type	-	Synthetic	Synthetic
Appearance	Visual	Smooth & Homogenous	Smooth & Homogenous
Colour	Visual	Black	Black
Work Penetration @25°C	ASTM D217	390	310 - 340
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b	1b
Dropping Point °C, Min	ASTM D2265	N/A	190
Four Ball Weld Load, Kg, Min	ASTM D2596	400	400
Molybdenum Content, %Wt.	ASTM D7303	5	5
Operating Temperature Range °C	INTERNAL	-50 to 130	-40 to 130
Base Oil Viscosity @40°C (Cst)	ASTM D445	150	150

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.