



ATRIX SYN PU 460

PRODUCT DESCRIPTION:

ATRIX SYN PU 460 is a synthetic, high-performance grease designed for long-lasting performance in fill-for-life applications across a wide range of industrial settings. Formulated with synthetic, high-viscosity base oils and performance additives, this grease delivers exceptional longevity and reliability. It also boasts excellent water resistance and water washout characteristics. ATRIX SYN PU 460 is ideal for use in steel, paper, and wind power industries, as well as for heavy-duty, slow-moving plain and rolling element bearings operating in severe environments.

APPLICATIONS

ATRIX SYN PU 460 grease is recommended for steel, paper, wind power applications as well as heavy duty slow moving plain and rolling element bearings operating in severe environments.

PRODUCT ADVANTAGES

- The operating temperature range is -30°C to 150°C
- Outstanding high-temperature oxidation stability
- Excellent extreme pressure properties
- High dropping point
- Effective corrosion protection
- Long operational life

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE	
		1.5	2
NLGI Grade	ASTM D217		
Thickener Type	-	Di- Urea	Di- Urea
Base Oil Type	-	Fully Synthetic	Fully Synthetic
Appearance	Visual	Smooth & Homogenous	Smooth & Homogenous
Color	Visual	Light Brown	Light Brown
Work Penetration, 60 Strokes, 0.1mm	ASTM D217	305	265-295
Dropping Point °C, Min	ASTM D2265	250	250
Cu Corrosion	ASTM D4048	1b	1b
Oxidation Stability, Drop In Pressure, Psi	ASTM D942	max 5	max 5
Oil Separation, % Wt.	ASTM D6184	max 3	max 3
Operating Temperature Range °C	INTERNAL	-30 to 150	
Base Oil Viscosity @40°C (Cst)	ASTM D445	460	460

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.