



AVEX ATF+4 SYNTHETIC

PRODUCT DESCRIPTION:

AVEX ATF+4 is an automatic transmission fluid designed for use in a wide range of Japanese, Korean, and Chrysler vehicles that require ATF+4 or earlier specifications. This fluid offers excellent low-temperature performance and enhanced anti-shudder properties. AVEX ATF+4 is also recommended for use in transmissions, hydraulic systems, and power steering units of American, European, Korean, Japanese, and other vehicles worldwide that specify Chrysler ATF+4, ATF+3, or ATF+2 fluids.

FEATURES & BENEFITS:

- Excellent flow properties at low start-up temperatures and high operating temperatures
- Improved shift performance and vehicle drivability/improved shudder performance
- Good viscosity stability
- Excellent oxidation stability, less fluid breakdown in high-temperature service
- Dependable protection against rust and corrosion
- Provides more assured wear protection for maximum transmission/transaxle life
- Engineered with superior base oils to ensure superb low and high temperature performance

APPLICATION:

- Automatic transmissions specially formulated for Chrysler vehicles, including Dodge, Plymouth, Eagle and certain Jeeps, that require a fluid meeting ATF+4 specification.
- Mitsubishi and Hyundai applications where an MS-9602 type fluid is specified.
- Services that specify an ATF+, ATF+2 and ATF+3 type fluid, including certain manual transmissions, transfer cases and power steering units (1999 and later).

PERFORMANCE LEVELS: Meets or Exceeds:

- Chrysler ATF+4® Requirements
- Chrysler MS-9602

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	AVEX ATF+4
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	7.30
Viscosity Index (min)	ASTM D2270	-	140
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR
Flash Point (min)	ASTM D92	°C	200
Pour Point (max)	ASTM D97	°C	-42
Viscosity Brookfield @ -40 °C	ASTM D2983	mPa.s (cP)	8400

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.