



AVEX DEXRON II D MINERAL

PRODUCT DESCRIPTION:

AVEX DEXRON II D is a high-quality automatic transmission fluid formulated with highly refined base stocks and advanced additive technology. Designed for use in passenger cars and light commercial vehicles, it effectively reduces transmission "chatter," ensuring smooth and quiet operation at all speeds and under various conditions. AVEX DEXRON II D offers excellent oxidation and thermal stability, friction control, system cleanliness, load-carrying capability, and superior wear and corrosion protection, extending the lifespan of your transmission.

APPLICATION:

Suitable for automatic gearboxes of passenger cars, power steering, vans, truck and buses where the manufacturer recommends an ATF GM Dexron II D.

FEATURES & BENEFITS:

- Very high viscosity index linked with an excellent viscosity stability in operation
- Very low pour point
- Very good thermal stability
- Excellent resistance to oxidation
- Friction properties specific to the requirements.

PERFORMANCE LEVELS: Meets or Exceeds:

- GM DEXRON IID
- CHRYSLER +3
- VOITH H55.6335
- VOLVO 97355
- FORD ESP-M2C138-CJ / ESP-M2C166-H
- ALLISON TES 389, ALLISON TES 228(C4)
- MB 236.1/236.5/236.7
- ZF TE-ML-04D / 09 / 11A / 14A
- BMW 81 22 9 400 272/81 22 9 400 275/81 22 9 407 738
- CAT TO-2
- TOYOTA TII/2
- MAN 339 TYPE L2/V1
- OPEL 19 40 700 / 19 40 707
- MITSUBISHI SP / SP2/ BTR

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	AVEX DEXRON II D
Kinematic Viscosity @ 104°F / 40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F / 100°C, min	ASTM D7042	cSvt	7.1
Viscosity Index	ASTM D2270	-	140
Density@15°C/ 60°F	ASTM D4052	g/cm³	TBR
Flash Point (min)	ASTM D92	°C	200
Pour Point (max)	ASTM D97	°C	-42

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.