



AXENT MULTI MULTIFUNCTION HYDRAULIC FLUID

PRODUCT DESCRIPTION:

AXENT MULTI is a high-performance, multifunctional synthetic-based hydraulic fluid specifically designed for modern vehicles equipped with hydraulic systems, including power steering, hydraulic dampers, suspensions, hard tops, and centralized hydraulic systems.

APPLICATION:

This product is highly recommended for use with the following European OEMs: VW (VAG), Audi, Porsche, BMW, Citroën, Mercedes, Mini, Peugeot, Volvo, and Saab, as well as American manufacturers such as Ford and General Motors-Opel.

FEATURES & BENEFITS:

- Protects hydraulic pumps heavily loaded.
- Extends life time duration of all systems.
- Provide comfort and noise reduction especially at cold conditions.
- Provide outstanding anti-wear, anti-corrosion and anti-foam properties.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

DIN	51 524 T2, 51 524 T3
ISO	7308
AUDI	G 002 000, G 00 4000, TL 52 146
BENTLEY	RH 5000, TH 5000
BMW	54 34 0 392 235, 54 34 0 394 395, 54 34 7 117 733, 81 22 9 407 758, 82 11 0 148 132, 82 11 1 468 041, 83 29 0 429 576
CHRYSLER	05127381AB, 68088485AA, MS 10838, MS 11655, MS 5931
CITROEN	9730 A5, 9735-EJ, 9735-EJ, 99 7969, 9979-A1, 9979 A4, H 50126, PSA S71 2710, Total Fluide DA, Total Fluide LDS
DODGE	MS 11655
DS (CAPSA)	9730 A5, 99 7969, 9979 A4, H 50126, Total Fluide DA, Total Fluide LDS
FENDT	X 902 011 622
FIAT	9.55550-SA1, Tutela GI/R
FORD	WSS-M2C204-A
FUCHS	Rave ZH 3044, Rave ZH 4300 B
GENERAL MOTORS	B 040 0070, B 040 0070, B 040 2012, GM 1940715, GM 1940766
HYUNDAI	00232-19017, PSF-4
JEEP	MS 11655
KIA	00232-19017, PSF-4
LAND ROVER	Cold Climate PAS Fluid LRN2261, LR003401
LEXUS	PSA S71 2710, PSF NEW-W
MAN	M 3289 (3623/93)
MERCEDES-BENZ	001 989 24 03 10, 001 989 24 03 12, MB 345.0, Q 1 32 0001
MINI	54 34 0 392 235, 54 34 0 394 395, 54 34 7 117 733, 81 22 9 407 758, 82 11 0 148 132, 82 11 1 468 041, 83 29 0 429 576
OPEL	B 040 0070, B 040 2012, GM 1940 715, GM 1940 766
PEUGEOT	9730 A5, 9735-EJ, 99 7969, 9979 A4, H 50126, PSA S71 2710, Total Fluide DA, Total Fluide LDS
PORSCHE	000 043 203 33, 000 043 206 56
SAAB	3032 380, 93160548
SEAT	G 002 000, G 004 000, G 004 012, TL 52 146
SKODA	G 002 000, G 004 000, G 004 012, TL 52 146
TOYOTA	PSA S71 2710, PSF NEW-W
VOLVO	1161529, 1273 36, 30741424
VW	G 002 000, G 004 000, G 004 012, TL 52 146, TL 52 146
ZF	TE-ML 02K

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	AXENT MULTI
Kinematic Viscosity @100C	D445	cSt	6.2
Kinematic Viscosity @40C	D445	cSt	19
Viscosity Index	D1120	-	320
Density@20C	D1298	g/cm3	TBR
Flash Point (min)	D92	°C	154

DISCLAIMER: The test data presented above is for reference only and not a specification. It may vary within acceptable production tolerances. Alpha reserves the right to update this data, with the latest version of the Technical Data Sheet (TDS) taking precedence over previous versions.

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil may lead to skin issues. Avoid contact. If contact occurs, wash immediately with soap and water. Do not dispose of used oil in drains or the environment. Instead, take it to an authorized oil collection facility. For more safety information, please refer to the MSDS available on our website: www.alphaoil.ae

HEALTH & SAFETY:

When used correctly in the recommended application and with proper personal hygiene, this product is unlikely to pose significant health or safety risks. For detailed safety information, refer to the Safety Data Sheet (SDS), available upon request from your local sales office or online. www.alphaoil.ae

PROTECT THE ENVIRONMENT:

Dispose of used oil at an authorized collection point. Follow local regulations and avoid releasing it into drains, soil, or water.

STORAGE:

We recommend storing all packages under cover. If outdoor storage is necessary, drums should be placed horizontally to prevent water ingress and protect drum markings. Products should not be stored above 60°C or exposed to direct sunlight or freezing conditions.